

THE STYLE LS spiral wound gasket was developed as a high integrity, low seating stress alternative to traditional sheet gaskets used in Class 150 and 300 service, where there may be concern about exceeding allowable design bolt stresses or overstressing the flanges. The LS gasket gasket has the inherent strength, resiliency, and blowout resistance of standard spiral wound gaskets, but requires a bolt stress of only 25,000 psi on standard ASME B16.5 flanges.

The Flexitallic Style LS spiral wound gasket is covered under U.S. Patents 5161807 and 5275423; worldwide patents pending.

Maximum P/T Limits

	Material	Max T	Max P
Fillers	PTFE	500°F (260°C)	The same as pressure limits of corresponding ASME flanges
	Flexicarb	900°F (482°C)	
	Others	Other fillers available	
Metals	Carbon Steel	1000°F (537°C)	
	304 SS	1000°F (537°C)	
	304L SS	1000°F (537°C)	
	316L SS	1500°F (815°C)	
	321 SS	1600°F (870°C)	
	347 SS	1600°F (870°C)	
	410 SS	1560°F (848°C)	
	Alloy 20	1400°F (760°C)	
	Monel	1500°F (815°C)	
	Titanium	2000°F (1092°C)	
	Nickel	1200°F (650°C)	
	Inconel 600	2000°F (1092°C)	
	Inconel 625	2000°F (1092°C)	
Inconel X-750	2000°F (1092°C)		
Hastelloy B2	2000°F (1092°C)		
Hastelloy C276	2000°F (1092°C)		
Incoloy 800	2000°F (1092°C)		
Incoloy 825	2000°F (1092°C)		

Required Surface Finish

125 - 250 Microinch Ra

Recommended Compressed Thickness

.125" - .135"

Size Range

Available with full range of standard sizes up to 24" for Class 150 & 300 ASME flanges. For larger sizes and odd shapes consult Flexitallic Technical Department.

Design Information

ASME Constants	m	3.0	
	Y	5,000 psi (34.50 MPa)	
PVRC Constants		SS/Flexicarb	SS/PTFE (LSI)
	G _b	598 psi (4.1 MPa)	698 psi (4.8 MPa)
	a	0.385	0.249
	G _s	0.030 psi	1.28 x 10 ⁻³ psi (0.882 x 10 ⁻⁵ MPa)

This Data Sheet relates to the material as supplied. The information contained herein is given in good faith, but no liability will be accepted by the Company in relation to same. The acquisition of additional information may necessitate revisions to parts or all of this Data Sheet, and such information will be supplied as it becomes available.

As the Company's products are used for a multiplicity of purposes, and as the Company has no control over the method of their application or use, the Company excludes all conditions or warranties, express or implied, by statute or otherwise, as to their products and/or their fitness for any particular purpose. Any technical co-operation between the Company and the Customer is given for the Customer's assistance only and without liability on the part of the Company.



Member of The Flexitallic Group