



VALVE LIFTERS

P: 0800 225 4357 F: (09)828 6469 E: auto@acl.co.nz

73 Lansford Crescent, Avondale, Auckland



CODE	MAKE	MODEL	TYPE	LENGTH	WIDTH
VL4883	BMC	998cc, 1098cc, 1275cc A-series	SOLID	38.10mm	20.58mm/.810"
VL41	BUICK	V8 (same as Rover and Leyland P76)	hydraulic	50.80mm	21.40mm/.842"
VL37	CHEVROLET	Small and Big block	hydraulic	50.80mm	21.40mm/.842"
VL89	CHRYSLER	245,265 6cyl & 273-360 V8	hydraulic	48.25mm	22.47mm/.885"
VL109	DAEWOO	A15SMS, G15MF, C20LE	hydraulic	68.70mm	21.40mm
VL146	DAIHATSU	FE/10/2/20 1.0	hydraulic	20.80mm	12.00mm
VL1474	FORD	Zodiac Capri, Essex V6	SOLID	50.80mm	21.00mm
VL1477	FORD	Anglia, Escort, Cortina (head size 21.5mm)	SOLID	47.40mm	11.06/.4375"
VL1498	FORD	Escort, Cortina x/flow (head size 22.40mm)	SOLID	47.10mm	13.08mm/.515"
VL35	FORD	Falcon 188/200/250 non X/flow 200/250 x/flow3 3-4.1 x/flow	hydraulic	50.90mm	22.20mm/.874"
VL35	FORD	Falcon 221-351Windsor, 302-351 Cleveland	hydraulic	50.90mm	22.20mm/.874"
VL390	FORD	Falcon 6 cyl EA-EB	hydraulic	31.00mm	14.00mm
VL4000	FORD	Falcon 6 cyl EB-on	hydraulic	26.30mm	11.00mm
VL9	FORD	Falcon 200-250 6 cyl non x/flow	hydraulic	46.50mm	22.20mm/.874"
VL109	HOLDEN	C12/14NZ, C14/16SE, C24SE, Y24SE, 16JH, 18JC, Holden 18le, 16lf, X20se, C20se	hydraulic	68.70mm	21.40mm
VL115	HOLDEN	VN 3.8 V6, 5.7 V8	hydraulic	66.10mm	21.40mm/.842"
VL6700	HOLDEN	Astra Vectra C18SE C20 X20XE	hydraulic	26.10mm	32.00mm
VL73	HOLDEN	173, 179, 186, 202 6 Cyl, 253, 308 V8	hydraulic	50.90mm	21.40mm/.842"
VL73SP	HOLDEN	173, 179, 186, 202 6 Cyl, 253, 308 V8 sealed power	hydraulic	50.90mm	21.40mm/.842"
VL135	HYUNDAI	G4CN/P/R, G6CT/U, G4IS	hydraulic	53.80mm	15.90mm
VL141	HYUNDAI	G4CS, G4EKT, G6AT 26mm	hydraulic	25.80mm	13.00mm
VL146	HYUNDAI	G4DJ, G4EK	hydraulic	20.80mm	12.00mm
VL146	ISUZU	6VD1 SOHC	hydraulic	20.80mm	12.00mm
VL135	KIA	G6 CU	hydraulic	53.80mm	15.90mm
VL146	KIA	B5 SOHC 8V	hydraulic	20.80mm	12.00mm
VL5010	KIA	K5 V6	hydraulic	24.20mm	33.00mm
VL41	LEYLAND	V8 P76 4.4L	hydraulic	50.80mm	21.40mm/.842"
VL4883	LEYLAND	998cc 1098cc 1275cc A-series	SOLID	38.10mm	20.58mm/.810"
VL146	MAZDA	B3-MI, B5, B6, BP, F2/T, F8, FE/D/T, G6, J2, B6Y/2E/ME, F8	hydraulic	20.80mm	12.00mm
VL149	MAZDA	B3-MI, B6/Y/2E/ME, B6D, B6T, BPT, K8, KF/ZE, KL	hydraulic	24.00mm	30.00mm
VL5010	MAZDA	FE-D 2.0 DOHC	hydraulic	24.20mm	33.00mm
VL135	MITSUBISHI	4G61/64 DOHC, 6G72/4 DOHC	hydraulic	53.80mm	15.90mm
VL136	MITSUBISHI	4G93 SOHC, 4G93T DOHC, 6A12	hydraulic	45.00mm	14.00mm
VL141	MITSUBISHI	4G15, 4G54, 4G62, 4G63, 4G64, 4G92sohc, 4G63T/BT, 4G64dohc, 6G72/74/75sohc	hydraulic	25.80mm	13.00mm
VL173	NISSAN	RB30/E/S, VG30E, RB30ET SOHC (head size 25.60mm)	hydraulic	49.00mm	16.00mm
VL6024	NISSAN	CA16/DE/18/DE, VG30DE/DETT, VG33E (head size 21.50mm)	hydraulic	48.20mm	15.90mm
VL6200	NISSAN	SR20DE/DET, VE30DE	hydraulic	44.80mm	16.98mm
VL41	ROVER	V8, 3.5L, 3.9L, 4.6L	hydraulic	50.80mm	21.40mm/.842"
VL5010	ROVER	KV6	hydraulic	24.20mm	33.00mm
VL146	SUBARU	EJ16/E/Jsoc, EJ18/Esoc, EJ20/201E, EJ202sohc	hydraulic	20.80mm	12.00mm
VL146	SUBARU	EJ22/Tsohc, 20.4x12dia EJ20T, EJ205, EJ207dohc	hydraulic	20.80mm	12.00mm
VL018	TOYOTA	1M2FE, 2T2FE, 2/3V2FE, 2R2FE, 3R2FE, 2J2GE, 3/5SFE, 4AF/FC/FE, 7AF	SOLID	31.00mm	24.50mm
VL73	TOYOTA	1Y, 2Y, 3Y, 4Y, 5K	hydraulic	50.90mm	21.40mm/.842"
VL41	TRUIMPH	V8-VITESSE V8, TR8	hydraulic	50.80mm	21.40mm/.842"